



Sandstone and Pre-Cast Concrete

---

## HANDY HINTS FOR ASSEMBLING A WALL FOUNTAIN F6005+F6006

---

*NOTE! These handy hints are designed as a guide only to assist smooth and precise construction.*

|                   |   |
|-------------------|---|
| <b>Bowl</b>       | <p>Determine the desired height of the fountain bowl.</p> <p>The stonework is fixed to brick or block work using galvanised pins.</p> <p>It is recommended at least four appropriate sized galvanised pins are installed under the bowl to take the majority of the bowls weight. These pin holes are pre-drilled. Use appropriate builders epoxy to secure pins into fluted bowl. Follow manufactures recommendation for curing times. If the wall fountain is to be secured to a timber wall, appropriate sized dyna bolts and washers or other fixing method will be required.</p> <p><i>NOTE! If using Dyna bolts the wall is not flat DO NOT tighten the bowl onto the wall as the uneven force will crack the bowl.</i></p> |
| <b>Back board</b> | <p>It is recommended that the backboard be secured with <b>at least</b> three suitably sized pins into the pre-drilled holes (the majority of the weight is supported by the pins underneath the bowl).</p> <p><i>NOTE! If using Dyna bolts DO NOT over tighten the backboard onto the wall as the uneven force will crack the backboard.</i></p>   |
| <b>Pump</b>       | <p>Install hoses before mounting items to wall.</p>   |

### **Suggested sequence:**

On the first day determine the position of the wall fountain and mark position on wall to locate supporting pins. Drill holes as required. Clean out holes thoroughly. Using approved builders epoxy, glue galvanised pins into pre-drilled holes and holes now drilled into masonry wall. Installed the pump into bowl and run cable if required down rebate section in rear face of fluted bowl. Mount fluted bowl into position and support with timber until the epoxy has fully cured. Ensure stone work is completely dry before application. Damp conditions will inhibit the set of epoxy. Second day, mount backboard with supplied pipe work to pump and secure to masonry wall in same way as fluted bowl.